



J A N U S e t C i e[®]

CARE & MAINTENANCE FOR WING

GLASS

Our tempered glass is a type of safety glass processed by controlled thermal or chemical treatments to increase its strength, and it is four times stronger than regular glass. We offer clear and ultra-clear sanded and painted glass that comes in different thicknesses, from 3/16 inch thick to one inch thick with a variety of edgework like flat polished and beveled edge.

CLEAR GLASS

ROUTINE CARE & MAINTENANCE

- Use a soft cloth and any normal household glass cleaning product such as Windex® to clean your clear glass
- You can also use mild, pH-neutral soap such as Dawn® and clean water
- Be careful of overspray and wipe off any fluid that gets on the frame

EXTENSIVE CARE & MAINTENANCE

- If stains persist, most can be removed by blotting the stained areas with a dampened soft cloth soaked with vinegar or lemon juice
- For light scratches, use a buffing compound such as car wax
- Using the buffer with 6,000 grit sandpaper, lightly buff the glass until scratches disappear

SANDED OR PAINTED GLASS

The sanded or painted side of the glass should always face down; it should never be used as the top (i.e. the work surface). This is because it can scratch, and also because stains and dirt on the sanded side are more difficult to clean than on the top side. Avoid the use of any sharp tools on the sanded top side of the glass.

ROUTINE CARE & MAINTENANCE

- Use a soft cloth and clean water to remove light dust or dirt
- For more persistent dirt and grime, use water mixed with mild, pH-neutral soap such as Dawn® and clean water
- Avoid abrasive or harsh chemicals on the sanded side; they can abrade and even remove the finish

EXTENSIVE CARE & MAINTENANCE

- If stains persist, most can be removed by blotting the stained areas with a dampened soft cloth soaked with isopropyl alcohol to remove residue or marks

GLIDES

Our glides are constructed of high-quality materials including nylon, rubber, thermoplastic polyurethane, felt, or stainless steel. Glides can be fixed, adjustable or even self-leveling. Over time, the glides wear down and should be inspected frequently. If not, worn glides

can damage the furniture and flooring. Wear rates vary on flooring type and texture. When possible, lift furniture (rather than dragging) to move it.

ROUTINE CARE & MAINTENANCE

- Inspect frequently
- Replace worn glides as needed
- Replacement glides are available through your sales specialist

JANUSFIBER® & SYNTHETIC FIBER

Our synthetic fibers are not only recyclable, colorfast, UV-resistant, stain-resistant and suitable for humid and salty environments, but they also require minimal maintenance and endure beautifully in a range of temperatures. The fiber lineup includes proprietary handwoven JANUSfiber, made from high-density recyclable polyethylene.

ROUTINE CARE & MAINTENANCE

- Vacuum to remove loose dirt
- Prepare a cleaning solution of 2 ounces (1/4 cup) of mild, pH-neutral soap such as Dawn® and 8 cups of lukewarm clean water (less than 100°F/38°C)
- Use a sponge or soft cloth to clean
- Rinse thoroughly with clean water
- Allow to air dry

MECHANICAL JOINTS & MOVING PARTS

JANUS et Cie uses only the finest materials for its moving parts, hinges, hydraulic components, joints, folding mechanisms, poles, and drawer glides. Aluminum, marine brass, steel and stainless steel are wrought, cast, or extruded to create the ideal hardware components utilized on our furniture. Over time, these may loosen and require regular inspection and maintenance.

ROUTINE CARE & MAINTENANCE

- Use a sponge or soft bristle brush to brush away soil.
- Wash with mild, pH-neutral soap such as Dawn® and clean water using a non-abrasive cloth or sponge.
- Rinse thoroughly with clean water and pat dry with a non-abrasive cotton or microfiber cloth.
- After cleaning, inspect moving parts that may require lubrication.

PERIODIC CARE & MAINTENANCE

- Inspect moving parts and apply high-quality machine oil if needed.
- Inspect hardware and mechanical joints; tighten parts when necessary.

NATURAL STONE

JANUS et Cie uses a diverse mix of natural stone on our collections. Each stone brings its own beauty to the item. Our stone can vary in finish ranging from honed, polish or flamed. There are different levels of porousness in each stone, which can affect the amount of absorption and stain resistance. Some of our more porous materials are reinforced with an epoxy fill.

All of our stones are natural materials that we source from around the world. There can be variations in texture, color, veining, and patterns from one top to another. These differences and disparities are part of what makes the stone beautiful.

Our stone is treated with INTENSIFIATM by Dry-Treat. It is a combination of enhancer and sealer. This gives our stone a deep, long-lasting color enrichment and premium water- and oil-based stain protection. Our sealer does not protect the stone surface from being etched by acidic liquids or materials.

For installations in locations with continuous periods of freezing temperatures, cracks may occur in the natural stone with the expansion and contraction of the top as a result of these weather conditions. Storing your stone top indoors if possible or using a frame cover can help protect it during the off season or when not being used for extended timeframes.

Be wary of extreme changes in temperature as it could possibly damage your stone top. Using trivets and potholders is highly recommended to protect the stone when serving hot dishes. Coasters are also recommended to prevent possible water rings.

ROUTINE CARE & MAINTENANCE

- Use a microfiber cloth to dust off the surfaces.
- Wash with mild, pH-neutral soap such as Dawn® and clean water using a non-abrasive cloth or sponge.
- Use of harsh chemicals or abrasive cleaners is not recommended. They can scratch, pit, and etch the surface of the stone.
- Spills have the potential to stain. Porous stones are more susceptible to soaking up spills, which can discolor their surfaces. Clean spills immediately by wiping with a soft damp cloth.

EXTENSIVE CARE & MAINTENANCE

- We also recommend regularly cleaning with a stone cleaner formulated with a neutral pH, such as Oxy-Klenza Stone Cleaner (JeC Item #799-40-101-01-00). Please follow manufacturer's instructions.
- For stubborn stains on stone, a poultice of ammonia will remove most organic stains from marble. Dampen a paper towel or cloth with ammonia mixed with water, and cover the stain for 24-48 hours to remove. Household baking soda can absorb organic stains as well. Sprinkle the stained area with the baking soda and let it sit for 24-48 hours. Wipe clean and reseal (please refer to instructions below).
- Stone tops will need to be resealed based on use and environment. Before applying a new coat of INTENSIFIATM sealer (JeC Item #799-40-100-01-00), please make sure your stone top is clean. Follow the manufacturer's instructions. Depending on usage and location, this may need to be done multiple times a year. Please see your sales specialist for details.

CUSHIONS & FRAME COVERS

CUSHIONS

Available in all shapes, sizes, and styles, cushions are generally made of some sort of fill, some type of feathers, or some combination of these materials. Many different types of fills are available, each with a specific density and chemical formula designed and engineered to suit particular uses and different styles of furniture. Some foam cushions are just that, pieces of foam. Others are foam sandwiched in some sort of wrapping, such as Dacron, which provides loft and scale, and a softer profile. For thicker, more luxurious cushions, the optimal fill is a foam core enveloped in down or some soft synthetic; the wrapping is often stitched in channels like a sleeping bag to keep the cushion from shifting. As a rule, the fluffier the cushion is, the more casual its shape. The finest weather resistant materials have been used to make our cushions; however, they are not impervious to weather extremes or lack of maintenance. Cushions used on natural unseasoned teak and natural woods should be removed after each use until the wood has acclimated to its new environment. Cushions should be brought indoors during inclement weather.

ROUTINE CARE & MAINTENANCE / SPOT CLEANING

- Vacuum to remove loose dirt.
- Prepare a cleaning solution of 2 ounces (1/4 cup) mild, pH-neutral soap such as Dawn® per 1 gallon of lukewarm clean water (less than 80°F/30°C), or Use Faron Cleaner (JeC Item #799-90-100-00-00). If using Faron, please follow directions on bottle.
- Use a sponge to clean.
- Apply a light mist of cleaning solution as noted above using a spray bottle.

- Allow cleaning solution to soak into fabric.
- Work the solution into the stain by blotting or lightly scrubbing the area with a sponge.
- Rinse thoroughly with clean water.
- Blot excess moisture with a clean, soft white towel or sponge.
- Use a wet vacuum, if available, to remove excess moisture.
- Repeat these steps until stain is removed.
- Allow fabric to air dry.

PERIODIC CARE & MAINTENANCE

Cushions should never sit in water or be exposed to water for any prolonged period. To prevent mildew growth or any sort of possible damage to the furniture frames, always remove wet cushions from your furniture. If cushions become saturated with water, squeeze any excess water out of the cushions, then set them on their side to air dry in a well ventilated, clean, dry area. Drying times will vary, but may be accelerated if cushions are allowed to stand on edge in direct sunlight.

EXTENSIVE CARE & MAINTENANCE

JANUS et Cie solution dyed acrylic/polyester/polyolefin/polypropylene fabric cushion covers can be removed and washed; however, it may often be easier to clean the covers without removing them because they fit quite tightly and can be difficult to remove and replace. Please refer to fabric care and maintenance section for cleaning instructions of specific textiles.

In order to remove the foam insert from a cushion, gently fold the foam and pull the cover off, taking care not to allow the foam to overextend the zipper opening.

Clean cover by machine washing for acrylic, polyester, polyolefin or polypropylene fabrics with the cushion cover turned RIGHT SIDE OUT and AIR dry. DO NOT MACHINE DRY.

Replace the foam into the completely dry cushion cover by gently folding the foam and pulling the cover over the foam, taking care not to overstretch the zipper opening.

Reach into cover and gently tuck foam into cushion cover, matching the edges and corners to cushion cover shape, ensuring that all hems are turned in a uniform direction.

FURNITURE COVERS

Distinguished furniture covers embroidered with the JANUS et Cie logo make a distinctive statement while shielding your valuable investments from the elements. Durably constructed in high-performance fabric, our semi-fitted covers are as beautifully executed and flawlessly designed as our furnishings—each tailored with an elegant mini-welt finishing which belies the substantial zippers and strong fastening tabs that hold them securely to frames in windy conditions. Offered in a chic neutral tan or light grey, our covers are UV-resistant and meet industry standards to protect furniture from water, dirt, mildew and tearing.

ROUTINE CARE & MAINTENANCE

- Furniture covers should be removed from the frame and allowed to air out regularly to reduce the moisture under the cover. Moisture trapped under the cover due to climate can cause mold to grow under the cover.

PERIODIC CARE & MAINTENANCE

- Furniture cover should be removed to allow frames to dry out after inclement weather.

SPOT CLEANING

- Vacuum to remove loose dirt.

- Prepare a cleaning solution of 2 ounces (1/4 cup) mild, pH-neutral soap such as Dawn® per 1 gallon of lukewarm clean water (less than 80°F/30°C), or use Faron Cleaner (JeC Item #799-90-100-00-00). If using Faron, please follow directions on bottle.
- Use a sponge to clean.
- Apply a light mist of cleaning solution as noted above using a spray bottle.
- Allow cleaning solution to soak into fabric.
- Work the solution into the stain by blotting or lightly scrubbing the area with a sponge.
- Rinse thoroughly with clean water.
- Blot excess moisture with a clean, soft white towel or sponge.
- Use a wet vacuum, if available, to remove excess moisture.
- Repeat these steps until stain is removed.
- Allow fabric to air dry.

EXTENSIVE CARE & MAINTENANCE

- After extensive use and cleaning, JANUS et Cie furniture cover fabric could begin to lose its resistance to water. This can be replenished by applying Fabric Guard 303 (JeC Item #799-90-301-00-00).

TEXTILES

JANUS et Cie Textiles speak to our natural love of color, pattern, structure and texture—in the world, in the home and in our wardrobes. Our extensive collection of captivating textiles is designed to allow you to dress furniture and environments with the same variety and personality that you dress yourself! More than 200 fabrics comprise our collection including sumptuous Weatherskin® exterior faux leather. Our outdoor fabrics, ranging from brights to stripes and patterns to solids, are woven from solution dyed acrylic, polyolefin and polypropylene for a surface that resists microbes, soil, abrasion and fading from UV light. The result is perfect for hospitals, hotels, office spaces, and private residences. Our deep stock of textiles allows you to create a distinct and personal, elegant and vibrant interior or exterior setting.

JANUS et Cie fabrics do not promote mildew growth; however, mildew may grow on dirt and other foreign substances that are not removed from the fabric. JANUS et Cie fabrics are heat sensitive and will shrink when subjected to excessive heat. Never steam press or machine dry these fabrics.

SOLUTION DYED POLYPROPYLENE FABRIC

JANUS et Cie's polypropylene fabric is recyclable and produced from non-toxic and hypoallergenic materials, as well as being mold and stain resistant. Polypropylene fabrics should not be ironed or cleaned with bleach.

ROUTINE CARE & MAINTENANCE

- Vacuum to remove loose dirt.
- Prepare a cleaning solution of 2 ounces (1/4 cup) mild, pH-neutral soap such as Dawn® per 1 gallon of lukewarm clean water (less than 80°F/30°C), or Use Faron Cleaner (JeC Item #799-90-100-00-00). If using Faron, please follow directions on bottle.
- Use a sponge to clean.
- Apply a light mist of cleaning solution as noted above using a spray bottle.
- Allow cleaning solution to soak into fabric.
- Work the solution into the stain by blotting or lightly scrubbing the area with a sponge.
- Rinse thoroughly with clean water.
- Blot excess moisture with a clean, soft white towel or sponge.
- Use a wet vacuum, if available, to remove excess moisture.
- Repeat these steps until stain is removed.
- Allow fabric to air dry.

PERIODIC CARE & MAINTENANCE

Repeated washings with liquid detergent may reduce the effectiveness of the soil-resistant and waterrepellent qualities, so it may be necessary to reapply a water-repellent finish, such as 303 Hi-Tech Fabric Guard (JeC Item #799-90-301-00-00), or a similar soil-resistant treatment. Always refer to directions from manufacturer.

EXTENSIVE CARE & MAINTENANCE

- For more stubborn stains, polypropylene fabric can be machine washed with standard detergent and tumbled dry on low.
- Polypropylene fabric can be dry cleaned as long as Tetrachloroethylene is not used.
- Following is a guide to help aid you with stain removal for JANUS et Cie textiles and cushions.

WEATHERSKIN TEXTILES

Weatherskin is a durable high-tech fabric that looks and feels like soft glove leather. This product is designed with a built-in stain-resistant finish that will not wash or wear off and does not require a topically applied spray.

ROUTINE CARE & MAINTENANCE

Wash with mild, pH-neutral soap such as Dawn® and clean water using a non-abrasive cloth or sponge. Never use cleaners containing abrasives such as scouring powder or bleach.

PERIODIC CARE & MAINTENANCE

For water soluble stains, use a clean cloth or soft sponge to dab the stain with mild, pH-neutral soap such as Dawn® and clean water. Remove the soap solution by wiping the area with a cloth and clean water. Dry with a soft lint-free cloth or towel.

EXTENSIVE CARE & MAINTENANCE

- For oil-based or non-water soluble stains. First, test in the least visible area. Lightly wipe the stain with a clean cloth which has been moistened with a mild volatile solvent (acetone or paint thinner). Blot the area with a dry cloth and allow to air dry.
- For ink and magic marker, dab lightly with a cloth which has been moistened with a solution of one part dishwashing liquid and one part rubbing alcohol. DO NOT RUB. As the ink loosens, blot the area with a dry cloth. Repeat if necessary. Rinse with a cloth dampened in clean water and dry with a soft cloth.

SOLUTION DYED ACRYLIC, POLYESTER AND POLYOLEFIN TEXTILES

ROUTINE CARE & MAINTENANCE / SPOT CLEANING

- Vacuum to remove loose dirt.
- Prepare a cleaning solution of 2 ounces (1/4 cup) mild, pH-neutral soap such as Dawn® per 1 gallon of lukewarm clean water (less than 80°F/30°C), or Use Faron Cleaner (JeC Item #799-90-100-00-00). If using Faron, please follow directions on bottle.
- Use a sponge to clean.
- Apply a light mist of cleaning solution as noted above using a spray bottle.
- Allow cleaning solution to soak into fabric.
- Work the solution into the stain by blotting or lightly scrubbing the area with a sponge.
- Rinse thoroughly with clean water.
- Blot excess moisture with a clean, soft white towel or sponge.
- Use a wet vacuum, if available, to remove excess moisture.
- Repeat these steps until stain is removed.
- Allow fabric to air dry.
- Solution dyed acrylic, polyester and polyolefin should never be dry cleaned.

PERIODIC CARE & MAINTENANCE

Repeated washings with liquid detergent or bleach may reduce the effectiveness of the soil-resistant and water-repellent qualities, so it may be necessary to reapply a water-repellent finish, such as 303 Hi-Tech Fabric Guard (JeC Item #799-90-301-00-00), or a similar soil-resistant treatment. Always refer to directions from manufacturer. We offer McMaster® Stainless Steel Wipes (JeC Item #799-30-200-00-00), which clean and offer added protection against rust buildup. Follow instructions on packaging.

EXTENSIVE CARE AND MAINTENANCE

Heavy cleaning for stubborn stains and mildew (Excludes Weatherskin and polypropylene fabrics)

- Prepare a deep cleaning solution of 8 ounces (1 cup) of bleach and 2 ounces (1/4 cup) of mild, pH-neutral soap such as Dawn® per 1 gallon of clean water.
- Spray on entire area and allow to soak into the fabric for 15 minutes to 1 hour.
- Thoroughly yet gently, rub in deep cleaning solution with a soft bristle brush, sponge, or clean towel.
- It is best to clean the entire surface area of the fabric to avoid water rings and stains.
- Rinse thoroughly with clean water.
- Allow fabric to air dry in a well ventilated, clean, dry area.
- If stain and/or mildew persist, bleach quantities may be increased. In some cases, long standing stains may not be completely removable.